

Classic Resin

TR4070

Product Description

This product carries widespread agency approval, including meeting the FDA's requirements for indirect food contact. In addition to superior performance for compliance applications, this ribbon eliminates the need for overlaminates. It also features our specially formulated backcoat technology and exclusive anti-static properties for easy handling and unrivaled printhead protection.

Recommended Applications



Automotive



Chemicals



Compliance



Electronics



Inventory & Logistics



Pharmaceutical



Health & Beauty

Product Features

Anti-static	✓
High-density	✓
Printhead Protection	✓
Proprietary Backcoat	✓
Scratch Resistant	✓
Smudge Resistant	✓

Recommended Substrates

Economy Synthetics	Polyester
Specialty Materials	Polyimide Top-coated Vinyl

Ribbon Properties

Ink	Resin
Color	Black
Base Film Thickness	4.5 ± 0.4μ
Ink Thickness	1.8 ± 0.5μ
Total Thickness	6.3 ± 0.9μ
Ink Transfer Temperature	Uncoated Tag 134°C (273°F)

Product Compliance

- Compliant with REACH, RoHS and FDA (indirect food contact) regulations
- BS5609 certified and GHS compliant with FLEXcon DRUMcal 51932 and MACtac FCD6914
- UL and cUL Labeling References:
 - 3M file #PGJI2.MH16411, PGJI2.MH18072, PGJI2.MH45276
 - Avery file #PGJI8.MH17205, PGJI8.MH20558, PGJI8.MH20580, PGJI8.MH26285, PGJI8.MH27538
 - FLEXcon file #PGJI2.MH16635
 - MACtac® file #PGJI2.MH2676
 - UPM Raflatac file #PGJI2.MH26760

Pacific Barcode Inc.



Label Printing Solutions

27531 Enterprise Circle W, Temecula, CA 92590
sales@pacificbarcode.com · pacificbarcode.com
800.508.2535