

# TSC

The Smarter Choice.

**Pacific Barcode, Inc**



1-800-508-2535

sales@pacificbarcode.com  
www.pacificbarcode.com



## **TTP-245C SERIES** – Desktop Thermal Transfer Bar Code Printer **THE PERFECT FIT!**



### **KEY FEATURES**

- Perfect size – space saving design
- Fast Processor 200 MHz
- Standard memory of 4 MB Flash, 8 MB SDRAM and SD card reader for memory expansion up to 4 GB
- High quality double-walled clamshell design
- Easy ribbon loading
- Easy media loading
- Durability and reliability
- USB 2.0, serial, parallel and Ethernet interfaces are standard
- Powerful firmware: TSPL-EZ™, file manager, BASIC programming, stand-alone programming
- 2-year limited warranty
- ENERGY STAR® qualified

### **APPLICATIONS**

- Point-Of-Sale
- Product Marking
- Receipt / Coupon Printing
- Compliance Labeling
- Asset Tracking
- Document Management
- Shipping / Receiving
- Specimen Labeling
- Inventory Control
- Patient Tracking

# TTP-245C SERIES – Desktop Thermal Transfer Bar Code Printer

PRINTER MODEL	TTP-245C	TTP-343C	TTP-244CE (BASIC)	TTP-244CE (ADVANCED)
Resolution	8 dots/mm (203 DPI)	12 dots/mm (300 DPI)	8 dots/mm (203 DPI)	
Printing method	Thermal Transfer & Direct Thermal			
Max. print speed	152 mm (6")/second	102 mm (4")/second	102 mm (4")/second	
Max. print width	108 mm (4.25")	106 mm (4.17")	108 mm (4.25")	
Max. print length	2,286 mm (90")	1,016 mm (40")	2,286 mm (90")	
Enclosure	Double-walled plastic			
Physical dimension	202mm (W) x 173 mm (H) x 258 mm (D) 7.95" (W) x 6.81" (H) x 10.16" (D)			
Weight	2.3 kg (5.07 lbs)			
Label roll capacity	127 mm (5" ) OD			
Ribbon	110 m long, max. OD 40 mm, 0.5" core (ink coated outside)			
Ribbon width	40 mm ~ 110 mm (1.57" ~ 4.33")			
Processor	32-bit RISC CPU			
Memory	<ul style="list-style-type: none"> <li>4 MB Flash memory</li> <li>8 MB SDRAM</li> <li>SD Flash memory card reader for Flash memory expansion, up to 4 GB</li> </ul>		<ul style="list-style-type: none"> <li>4 MB Flash memory</li> <li>8 MB SDRAM</li> </ul>	<ul style="list-style-type: none"> <li>4 MB Flash memory</li> <li>8 MB SDRAM</li> <li>SD Flash memory card reader for Flash memory expansion, up to 4 GB</li> </ul>
Interface	<ul style="list-style-type: none"> <li>RS-232</li> <li>Centronics</li> <li>USB 2.0</li> <li>Internal Ethernet, 10/100 Mbps</li> <li>Bluetooth (user option)</li> <li>External 802.11 b/g/n wireless (user option)</li> </ul>		<ul style="list-style-type: none"> <li>USB 2.0</li> </ul>	<ul style="list-style-type: none"> <li>USB 2.0</li> <li>RS-232</li> <li>Centronics</li> <li>Internal Ethernet, 10/100 Mbps</li> <li>Bluetooth (user option)</li> <li>External 802.11 b/g/n wireless (user option)</li> </ul>
Power	External universal switching power supply <ul style="list-style-type: none"> <li>Input: AC 100-240V, 2.5A, 50-60 Hz</li> <li>Output: DC 24V 3.75A, 90W</li> </ul>		External universal switching power supply <ul style="list-style-type: none"> <li>Input: AC 100-240V, 2.5A, 50-60 Hz</li> <li>Output: DC 24V, 2.5A, 60W</li> </ul>	
Operation switch, button LED	1 power switch, 1 feed button & 1 LED (3 colors: green, amber & red)			
Sensors	<ul style="list-style-type: none"> <li>Gap transmissive sensor</li> <li>Black mark reflective sensor (position adjustable)</li> <li>Head open sensor</li> <li>Ribbon end sensor</li> </ul>			
Internal fonts	<ul style="list-style-type: none"> <li>8 alpha-numeric bitmap fonts</li> <li>Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font</li> </ul>			
Bar code	<ul style="list-style-type: none"> <li>1D bar code Code 39, Code 93, Code 128UCC, Code 128 subset A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2 (5) digits add-on, MSI, PLESSEY, POSTNET, GS1 DataBar, Logmars, Code 11</li> <li>2D bar code PDF-417, Maxicode, DataMatrix, QR code, Aztec</li> </ul>			
Font and barcode rotation	0, 90, 180, 270 degree			
Printer language	TSPL-EZ™			
Media type	Continuous, die-cut, tag & fan-fold (outside wound)			
Media width	20 ~ 112 mm (0.79" ~ 4.4")			
Media thickness	0.06 ~ 0.19 mm (2.36 ~ 7.48 mil)			
Media core diameter	25.4 ~ 38.1mm (1" ~ 1.5")			
Label length	10 ~ 2,286 mm (0.39" ~ 90")	10 ~ 1,016 mm (0.39" ~ 40")	10 ~ 2,286 mm (0.39" ~ 90")	
Environment condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing			
Safety regulation	FCC Class B, CE Class B, C-Tick Class B, UL, CUL, TÜV/Safety, CCC, ENERGY STAR®			
Environmental concern	Comply with RoHS, WEEE			
Accessories	<ul style="list-style-type: none"> <li>Windows labeling software CD disk</li> <li>Quick start guide</li> <li>External universal switching power supply</li> <li>USB cable</li> <li>Power cord</li> </ul>			
Limited warranty	<ul style="list-style-type: none"> <li>Printer: 2 years</li> <li>Print head: 25 km (1 million inches) or 12 months which comes first</li> <li>Platen: 50 km (2 million inches) or 12 months which comes first</li> </ul>			
Factory options	<ul style="list-style-type: none"> <li>Real time clock (standard in EMEA)</li> </ul>		<ul style="list-style-type: none"> <li>N/A</li> </ul>	
Dealer options	<ul style="list-style-type: none"> <li>Guillotine cutter (full cut or partial cut)</li> <li>Peel-off module</li> </ul>		<ul style="list-style-type: none"> <li>N/A</li> </ul>	
User options	<ul style="list-style-type: none"> <li>Bluetooth module (serial interface)</li> <li>802.11 b/g/n wireless module (serial interface)</li> <li>External media hanger with 3" OD label spindle</li> <li>KP-200 Plus series keyboard</li> <li>KU-007 Plus programmable smart keyboard</li> </ul>		<ul style="list-style-type: none"> <li>External media hanger with 3" OD label spindle</li> </ul>	<ul style="list-style-type: none"> <li>Guillotine cutter (full cut or partial cut)</li> <li>Peel-off module</li> <li>External media hanger with 3" OD label spindle</li> <li>Bluetooth module (serial interface)</li> <li>802.11 b/g/n wireless module (serial interface)</li> </ul>



## CORPORATE HEADQUARTERS

**TSC Auto ID Technology Co., Ltd.**  
Tel: +886 2 2218 6789  
E-mail: apac\_sales@tscprinters.com

## LI ZE PLANT

**TSC Auto ID Technology Co., Ltd.**  
Tel: +886 3 990 6677  
E-mail: apac\_sales@tscprinters.com

## AMERICAS

**TSC Auto ID Technology America Inc. Corporate Office**  
Tel: +1 909 612 9606  
E-mail: americas\_sales@tscprinters.com

## Orlando Office

Tel: +1 407 704 8918  
E-mail: americas\_sales@tscprinters.com

## CANADA

**TSC Auto ID Technology America Inc.**  
Tel: +1 909 612 9606  
E-mail: americas\_sales@tscprinters.com

## MEXICO

**TSC Mexico Representative Office**  
Tel: +52 (33) 3836 6682  
E-mail: americas\_sales@tscprinters.com

## BRAZIL

**TSC Brazil Representative Office**  
Tel: +55 (11) 9597 8098  
E-mail: americas\_sales@tscprinters.com

## EMEA

**TSC Auto ID Technology EMEA GmbH**  
Tel: +49 (0) 8106 37979 00  
E-mail: emea\_sales@tscprinters.com

## RUSSIA

**TSC Auto ID Technology EMEA GmbH**  
Tel: +7 915 422 8889  
E-mail: emea\_sales@tscprinters.com

## MIDDLE EAST

**TSC Auto ID Technology ME Ltd, FZE**  
Tel: +971 4 2533 069  
E-mail: emea\_sales@tscprinters.com

## ASIA PACIFIC

**TSC Auto ID Technology Co., Ltd.**  
Tel: +886 2 2218 6789  
E-mail: apac\_sales@tscprinters.com

## CHINA

**Tianjin TSC Auto ID Technology Co., Ltd.**  
Tel: +86 22 5981 6661  
E-mail: apac\_sales@tscprinters.com



**Pacific Barcode, Inc**



1-800-508-2535

sales@pacificbarcode.com  
www.pacificbarcode.com

TSC® is a trademark of TSC Auto ID Technology Co., Ltd.  
TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company.  
© 2015 TSC Auto ID Technology Co., Ltd.  
Product models and Specifications are subject to change without notice.  
Contact your TSC sales representative for specific information.